



approximate size

MINI 4

The **MINI 4** is small, lightweight, easy to carry and user friendly. This small radio is robust with features such as 16 channels, high/low power settings, scan, battery save mode, wireless cloning and a proceed-to-talk tone.

Key Features:

- · Black Housing
- 16 Channels
- 1 Watt
- NEW! Customizable Face Plate
- Companding
- · Small only 4.75" tall
- · Lightweight only 2.4 oz.
- · Channel Scan (user selectable)
- NEW! Improved Accessory Jack (screw-in)
- NEW! Programmable speaker to work with a headset only
- User Menu (if enabled) with four programmable settings
- Single Board Construction
- · Wireless Cloning
- · Adjustable Microphone Sensitivity

One of the smallest, most affordable, and feature packed two-way radios available.

Accessories:





ellow Faceplate 221296

Green Faceplate

221292









Purple Faceplate 221293





221290



Silver Faceplate 221295



209241











Waterproof Carrying Bag 221123

MINI 4 106251

Specifications:

Additional accessories including wired headsets are available at: www.advancedwireless.com

Housing Color	Black
Dimension (inches)	
Height (including antenna)	4.75"
Width	1.625"
Depth	0.75"
Weight (w/battery & antenna)	2.4 ounces
Antenna	Fixed
Audio Accessory Jack	Single Pin Screw On
Power Supply - Battery	Li-Ion 3.7V 800 mAH
Power	1 W
Channels	up to 16
Select Channels	Up/Down Buttons
Frequency	450-470MHz UHF Band
Battery Status Indicator	Yes
Built-in VOX	Yes
Battery Save Mode	Yes

ТОТ	Yes
Compander	Yes / Channel
Scan	Yes - add/delete
Busy Channel Lock-Out	Yes
Proceed to Talk Tone	Yes
Scramble	Yes
LCD	Yes - with Back Light
Temporary Local Audio Reduction	Yes
CTCSS & DCS Coding	Yes
Keylock	Yes
Adjustable Microphone Gain (Sensitivity)	Yes
Wireless Cloning	Yes
Channel Spacing	12.5 KHz
Operating Voltage	3.7 V

Battery Life 5.5.90 Battery Save - ON	Low - 17 hours Medium - 15 hours High - 13 hours
Frequency Stability	±2.5ppm
Operating Temperature	-20°C to +55°C
Antenna Impedance	50Ω
Modulation	11K0F3E/6K00F3E
Spurious and Harmonics	≤-36dBm
FM Noise	≥40dB
Audio Distortion	≤5%
Sensitivity	0.25 μV
Selectivity	55dB
Inter Modulation	60dB
S/N	≥45dB
Rated Audio Power Output	500mW



(952) 469-5400 / (800) 475-5852 20809 Kensington Blvd, Lakeville, MN 55044 www.advancedwireless.com f ♥ in □





Armband 209586

Reversible Ear Hook 221203