

OTTO[®]



STORM[™] Speaker Microphone

Delivers Clear Communications In Extreme Conditions



**Easily
Accessible PTT**



**Outstanding
Durability**



IP68

**IP68 Water
Resistant**



**IS/ATEX
Available**

Designed for rugged use in harsh environments

When transmission clarity is imperative, OTTO's Storm speaker microphone delivers. This high-performance model is designed to provide clear communications for professional users in law enforcement, military and federal agency environments.

The Storm features a durable outer casing that is ergonomically designed for easy handling and use in active situations. The omnidirectional microphone eliminates the need to hold the speaker mic to the mouth. It easily captures voice commands from any angle to ensure outgoing communications are clearly heard and understood. The samarium cobalt, high-output speaker offers exceptional moisture and corrosion resistance to provide improved voice clarity and intelligibility for incoming communications.

The Storm may be configured for use with a wide range of two-way radios, and an IS/ATEX-certified model is also available.



Features

- Durable fully sealed housing has a built-in debris screen to keep dust, dirt and moisture from impacting communications clarity.
- Strong clothing clip rotates 360 degrees with positive stops every 45 degrees to allow precise positioning for safety.
- Strong coiled cable resists abrasion, strain and coil sag.
- Standard 2.5mm earphone jack is isolated from the main housing and includes seal for protection in wet conditions. 3.5mm jack is available for some radio models.
- Optional emergency button and/or antenna connector are available for selected radio models.
- Compatible with a variety of two-way radio models.

The **Storm** speaker microphone is ideal for personnel working in hazardous and extreme environments including water rescues, disaster recovery, fire and emergency situations. It features a large, textured PTT button, and side-mount push-button volume control that are both easy to locate and operate even when wearing gloves.

You can trust the Storm for reliable performance in situations that are immediately dangerous to life and health.

Specifications

- Immersion tested and fully sealed per IP68 standards; for accessory only. Rating may or may be for the connector
- Meets MIL-STD-810G for high performance in harsh environmental conditions including high temperatures and 40 mph blowing rain
- PTT Switch Life Cycle: 500,000 cycles
- Omnidirectional microphone reduces ambient noise
- Microphone Sensitivity @94 dB SPL: -40 dBV Typical
- IS/ATEX-certified model available
- Cable Pull Strength: 40 lbs. from both ends
- Operating Temperature: -30° C to +60° C
- Storage Temperature: -57° C to +60° C
- 3-year warranty



Engineered and Manufactured in the U.S.A. for Over 50 Years.

www.otto-comm.com | Toll-free: **+1-888-234-6886** | Direct: **+1-847-428-7171**

©2020 OTTO Engineering, Inc. All rights reserved.